C.CRANE

CCRadio-SWP

Pocket Radio



INSTRUCTION MANUAL

PLEASE READ ALL THE INSTRUCTIONS
COMPLETELY BEFORE USE
AND SAVE THIS MANUAL
FOR FUTURE REFERENCE.



Before Use



Please read IMPORTANT SAFETY INSTRUCTIONS on pages 23-25 before use. It is important to read and understand all instructions. Keep these precautions and instructions where all who use this radio will read them

WARNING: TO PREVENT FIRE OR ELECTRIC SHOCK HAZARD, DO NOT EXPOSE THIS PRODUCT TO RAIN OR MOISTURE.

CAUTION

RISK OF ELECTRIC SHOCK DO NOT OPEN

CAUTION: TO REDUCE THE RISK OF ELECTRIC SHOCK, DO NOT REMOVE THE RADIO BACK. NO USER SERVICEABLE PARTS INSIDE. REFER SERVICING TO QUALIFIED SERVICE PERSONNEL.



THE LIGHTNING FLASH AND ARROW-HEAD WITHIN THE TRIANGLE IS A WARNING SIGN ALERTING YOU OF "DANGEROUS VOLTAGE" INSIDE THE RADIO.



THE EXCLAMATION POINT WITHIN THE TRIANGLE IS A WARNING SIGN ALERTING YOU OF IMPORTANT INSTRUCTIONS ACCOMPANYING THIS RADIO.

For your future reference:

Serial No.				
	(found inside battery compartment)			
Date of Purchase				
Name & Address of Dealer				
Traine a radiose of Bodier				

Unpacking

The box should contain the CCRadio-SWP, earbuds, carry pouch and this manual. If anything is missing or damaged, please contact your dealer immediately. We recommend you keep the box in the unlikely event your radio needs to be serviced.

Copyright © 2007 by C. Crane Company, Inc. 1001 Main St, Fortuna, CA 95540

Phone: 1-800-522-8863 Web: *ccrane.com*

All rights reserved. No part of this booklet may be reproduced, in any form or means whatsoever, without permission in writing from C. Crane Company, Inc.


Quick Start

- **1.** Slide **(**pg. 10) "SENSITIVITY" switch to "DX" position.
- 2. Install two AA batteries in the battery compartment, paying close attention to orientation of the batteries' + and ends.
- **3.** Turn on the radio by pressing the **1** POWER button.
- 4. Adjust 8 "VOLUME"
- **5.** Select band by pressing the **1** BAND button
- **6.** Use the **2** "TUNING" knob to locate a station or by directly entering a frequency:
 - a) First, select the 1 BAND you want

 - c) Enter the frequency on the13 keyboard.

Table of Contents

Unpacking 3				
Quick Start4				
Radio Identification 6-11				
Features and Operation Explained				
Introduction				
Saving Stations to Memory 14				
Display Button 15				
Setting the Alarm 16				
Favorites 16				
Up and Down Buttons 17				
Band Button 17				
Frequency Button 18				
0-9 Keys 18				
Performance Tips 19-20				
Troubleshooting Guide 21				
Specifications22				
Power Adapter 22				
Safety Instructions 23-25				
Shortwave Tips 26-27				
Station Log 28-31				



POWER and SLEEP Timer

TUNING Knob LIGHT Button 6

MEMORY, TIME SET Button DISPLAY, Time, Frequency,

Alarm, AM Step, 12/24 Hour G

ALARM, (De)Activate Alarm, Set Alarm Time

FAVORITES, Tune Memories only VOLUME, Up and Down **@**

UP A, Frequency, Time, Memory Tune DOWN V, Frequency, Time, Memory Tune


8

BAND, Change Bands, 9-10 kHz steps

"FREQ" UENCY, Press to enter 8


0-9 KEYS, Direct Frequency and Memory access Frequency @

LCD Display 0




9	FM STEREO indicator, displays	8	& kHz indicates Kilohertz while in AM
	only when headphones are used		and SW bands only
9	TUNE indicator means a	(3)	MHz indicates Megahertz in FM band
	station or noise is high	8	Time or Frequency display
0	SLEEP FUNCTION indicator	8	AM/PM show while in 12 hour
9	AL means alarm is active		time format
9	AUTO, Radio alarm or goes to	8	SWI or SWII, indicates Shortwave I
	Buzzer, if radio is already "on"		or Shortwave II
8	BUZZER •) indicates buzzer	8	MW indicates "AM" in U.S.
	type alarm		(medium wave)
3	LOCK switch is "on"	@	FM indicates radio is in FM band
8	M.SCAN (FAVORITES), tunes	3	BATTERY flashing indicates batteries
	memorized stations only		are low
8	Indicates memory channel num-		
	ber 00-199 for Memory Stations		

Radio Identification - Sides



- 32 DX - LOCAL switches Sensitivity of SW and FM bands
- EARPHONE jack
- DC Power Jack, 3 Volts, Tip Negative
 TUNING KNOB adjusts Frequency, Time, Presets
- **3** BASS - NORMAL Switch, select for best sound
- **3** LOCK, press to lock, hold for 1 second to unlock

Radio Identification - Back



- WHIP ANTENNA used for FM and SW bands
- BATTERY COMPARTMENT LOCATION, insert 2 "AA" batteries
- RESET HOLE for resetting radio (located on bottom of radio)

Introduction

The CCRadio-SWP is the perfect size for packing around. It is unusually good at picking up stations. Audio is clear for its size, while taking as long as 70 hours to wear down a set of two AA batteries. Using the Tuning knob can be wearisome as it is with any small radio. The SWP has a novel way to zip around the bands to your favorite stations. "FAVORITES" (Memory Scan) can be used to guickly access all of your AM/FM and SW stations rapidly and across bands without pressing buttons. We encourage you to learn how to memorize a station (page 14). You can then use the "FAVORITES" button and the Tuning Knob to quickly scan your memory presets.



POWER • SLEEP Button

When you press and release the "POWER" button the first time, you will see "on" displayed for about two seconds. Press the "POWER" button again to turn the radio off.

To change to a "SLEEP" setting, press "POWER" again during the short time the "on" is displayed. It will first show "90" minutes and then decrease by five minutes for

each successive press. You have a choice of "on", and from 90 minutes down to 5 minutes by 5-minute steps. Stop on the setting you desire and it will be remembered for your convenience each time you turn the radio "on" again. If you select any one of the sleep settings, except "on", the SLEEP symbol "will be displayed while the radio is "on". When "on" is selected, the radio will simply turn on and off each time the power button is pushed.

Pressing the "POWER • SLEEP" button while the radio is operating on any of the SLEEP settings will turn the radio off.

2 TUNING KNOB

Turn the Tuning Knob while the radio is on to tune to a different frequency.

When setting the clock or alarm, it is also a good way to change the time, rather then using the up and down buttons.

The Tuning Knob also works when you have your favorite stations in memory. You can press "FAVORITES" and use the tuning knob to quickly access your memorized station. See page 16 for The "FAVORITES".

3 LIGHT

Pressing the "LIGHT" button will give you about eight seconds of light on the display.

SETTING CLOCK TIME/SAVING A STATION TO MEMORY

The **Memory/Time SET** key works in two ways:

- When the radio is "off" press and hold for one second until "Hour" flashes. You have eight seconds to set the hour. Use either the Tuning Knob or "UP" and "DOWN" buttons. Press again to set the minutes. Press a third time to confirm when done. You can change from 12 hour to 24 hour clock format by holding the "DISPLAY" button for five seconds.
- 2. When the radio is "on" the key is used to store a station into memory. First, tune to a station or frequency you want. Press "MEM T.SET and CH will blink in the upper right corner of the LCD display. Rotate the Tuning Knob to the memory channel where you want to store the station. The memory channels are numbered from "00" to "199". Press "MEM T.SET" again to finalize the memorized

station. There is a log in the back of this manual on pages 28-31 to help you organize your stations. Your memories will not be lost when batteries go dead or if you reset the radio.

5 DISPLAY button

The DISPLAY button works in two ways:

- When the radio is "on" the LCD display normally shows the frequency. Pressing the "DISPLAY" button will toggle the display through "ALARM TIME", "TIME" of day, and "SLEEP" timer status. It will show the minutes left on the "SLEEP" timer or "on" if the sleep timer is not being used.
- 2. When the radio is "off" the LCD display normally shows the time of day. Pressing the "DISPLAY" button will toggle the display through "ALARM TIME", tuning steps for AM, and your choice of 12 or 24 hour clock format. While the radio is "off", you can change from 12 hour to 24 hour clock format by holding the "DISPLAY" button for five seconds. Change it back using the same method. See "BAND" button on page 17 to change tuning steps for AM.

6 SETTING THE ALARM

You can activate or deactivate the alarm if the radio is "on" or "off". Pushing the "ALARM" button once sets the alarm to AUTO and the "radio" alarm. (The radio will alarm on the last station listened to.) A second push of the "ALARM" button sets the alarm to "buzzer" ((*. A third press of the "ALARM" button turns off both icons and the radio will not alarm. Press the "Power" button to stop the alarms when they come on. The alarm will not work if headphones are plugged in.

Set the alarm time with the radio "off". Press and hold the "ALARM" button for two seconds. Use the Tuning Knob to set the hours, press the "ALARM" button again and set the minutes. You must press the "ALARM" button again when done to confirm the "ALARM" time.

If the alarm is set to "AUTO" and you happen to have the radio "on" at the alarm time, then the buzzer will automatically come on, too.

7 FAVORITES

Pressing the "FAVORITES" key allows you to

tune the stations you have installed in memory exclusively. You can use the Tuning Knob, "Up" and "Down" buttons, or 0-9 Keys to change memory channels. This can save you much time if you are familiar with the stations in your area. There is no other function to this button. Press "FAVORITES" again to go back to regular tuning.

8 VOLUME

This is easy, up + and down -.

● UP A and ● DOWN V Buttons

These buttons can be used to tune the radio one step at a time or "press and hold" to scan for the next strong station.

The buttons can also be used when setting the time or to scroll through memorized stations while in **7** FAVORITES (Memory Scan) mode.

BAND button

Pressing the "BAND" button with the radio "on" changes bands in order: FM, AM, SW1, and SW2.

With the radio "off", the "BAND" button can be pressed and held for five seconds to

change the AM tuning steps from 10 to 9 kHz. The U.S. uses 10 kHz. Most of the rest of the world uses 9 kHz steps. It could be important to change the AM step rate if you use the "Up" and "Down" button to scan for stations and you happen to be in a foreign country.

#FREQ"UENCY Button

This is used to directly enter a frequency. You must be in the radio band of your choice before you enter a frequency. AM and SW is straightforward. Press "FREQ" and enter the AM or SW frequency using the numbered keys. For FM you must enter a last digit. To enter 100.3 FM you must press "FREQ" and then press 1-0-0-3.

1 0-9 KEYS

These are used to directly enter a frequency or memory channel. See
 "FREQ"-UENCY button for direct entry.

While in **7** FAVORITES (Memory Scan) mode you can also enter the channel number of a station you memorized. There is a programming quirk, however. Because there are 200 channels, you must key in 3 digits for each number. Channel "00" through "9"

must be entered with a "00" in front of the channel number. Channel numbers 10 through 19 must have a "0" entered in front of the channel number. Example: Channel "1" must be entered as 0-0-1.



Learning the features and the corresponding display icons can make your radio easier to use.

Performance Tips

While excellent for fine tuning, the Tuning Knob moves in only 1 kHz steps. Using the FAVORITES (Memory Scan) to dial right to your stations is a fast and easy method (page 16). You also have the ability to directly enter a frequency. See Shortwave Tips on page 26.

For best AM reception, rotate the radio for the clearest audio. If radio noise is present, try moving the radio to a better location so the noise decreases. Many times this is only a few inches or feet away. In a hotel room, try putting it in a window sill.

For FM, the telescopic antenna "up full"

Performance Tips

usually gives best reception. The antenna can also be rotated and shortened until the best signal is received.

Always fully extend the telescopic antenna for the best Shortwave reception. SW reception can easily be improved with the addition of a very simple antenna. A portable SW antenna available from C. Crane works well for travel.

Also, any insulated small diameter wire can be wound around the whip antenna and extended out 20' to 60'. The wire can be mounted on the inside of an outside wall or out a window and along the top of a nonmetal fence. Simple experimentation with the antenna wire location is the best way.

Most of the time, leave the DX-LOCAL switch set on DX, unless you are receiving an overly strong station. This can keep the strong station from overdriving the radio and also help in listening to a weaker station that is next to a strong station.

The buttons can be somewhat hard to press. Check the LCD display to confirm that you have pressed it hard enough to register.

Troubleshooting Guide

This radio has a microprocessor. If the display disappears or has odd characters, try resetting the radio. Use a toothpick or paperclip to momentarily stick in the "reset" hole gently. It is located on the bottom of the radio. The radio can be "on" or "off" when this is done. There must be power to the radio either by AC Adapter or batteries.

NO AUDIO: Be sure the volume is up and headphone jack does not have something in it. The alarm will not work if headphones are plugged in.

RADIO WILL NOT COME ON: Be sure the "LOCK" switch is off. Press and hold for one second to turn "LOCK" off.

BATTERIES: Do not mix old batteries with new batteries. The battery icon tlashes when the batteries are low. You have 15 seconds to change a set of batteries or you may have to set the clock time again.

AC ADAPTER: Make sure it is fully plugged into the radio.

SENSITIVITY: Be sure DX-LOCAL switch is on "DX". DX is an abbreviation for "distance". Be sure the antenna is up fully for FM and SW.

Specifications

1. Frequency Coverage:

FM 70.0 ~ 108.0MHz

AM (MW) 522 ~ 1628kHz (9k step) 520 ~ 1710kHz (10k step)

SW1 2300 ~ 7500kHz

SW2 9200 ~ 22000kHz

2. S/N (Signal to Noise) Sensitivity:

FM > 10uV

AM > 1mv/m (this is extraordinary)

SW > 30uV

3. AM Selectivity: > 25dB

4. Number of Memories: 200

5. Power Source:

2 (AA Size) or LR2

DC IN: 3V 150mA, Tip (-) 3.5mm x 1.3mm

6. Built-in Speaker: 25ohm 0.5W

7. Earphone Socket: 3.5mm 32ohm

8. Dimensions: 4.75" W x 3" H x 1.2" D

Power Adapter

If you have purchased an optional AC-DC adapter, be sure it is the correct voltage. It should have an output of three Volts DC with the center negative, and not less than 150 MAh. Use only the recommended adapter. Otherwise it may damage the radio or cause a fire or electric shock.



READ BEFORE OPERATING EQUIPMENT SAVE THESE INSTRUCTIONS



To prevent damage to your radio or possible injury to you or others, read these safety precautions and instructions entirely before applying power to your radio. Keep these precautions and instructions where all who use this radio will read them.

- 1) COMMON CARE △
 - Check the radio, AC adapter, batteries and any accessories regularly. Do not use the radio if there is any sign of damage. Only operate in accordance with the instructions in this manual. Only use attachments or accessories specified by the manufacturer.
- 2) PROPER BATTERY HANDLING A Never mix different type of batteries or use old batteries with new. We recommend you remove batteries from the radio if you are not going to use the radio for one month or more.
- 3) DISCONNECT THE RADIO IN CASE OF MALFUNCTION △ If you smell or notice smoke, disconnect

Safety Instructions

the AC Adapter and remove the batteries immediately, taking care to avoid burns. Contact C. Crane Company or their representative for inspection and service before any future operation. Only use the AC-DC Adapter recommended with the unit and replace it if wires become frayed or exposed. It should have an output of three Volts DC with the center negative, and not less than 150 MAh. Use only the recommended adapter. Otherwise it may damage the radio or cause a fire or electric shock.

4) KEEP OUT OF REACH OF CHILDREN △

Dropping the radio can cause damage or injury. Keep the AC Adapter cord in a position so someone cannot trip and cause the radio to fall.

5) KEEP AWAY FROM WATER AND MOISTURE ⚠

Keep the radio dry. Liquids and moisture can damage the radio. If a liquid leaks into the radio do not operate and seek a qualified service shop. To clean the radio, remove the power and use a damp cloth on the exterior only.

Safety Instructions

6) KEEP AWAY FROM EXTREME TEMPERATURES △

Extreme temperatures can damage the radio. Do not leave or use the radio where it can be subjected to high or very cold temperatures.

7) DO NOT ATTEMPT TO SERVICE RADIO △

Refer all service work to a qualified service shop when the radio does not appear to operate normally, exhibits a change in performance or the radio has received damage. Never open the radio as this may expose you to dangerous voltages and this will void all warranties.

8) OUTSIDE ANTENNAS OR CABLES △

Outside antennas or cables that create a potential hazard should not be used with this radio unless installed by qualified personnel.

Shortwave Tips

The CCRadio-SWP covers all of the important international broadcast bands. A "*" symbol signifies where you most likely find the best listening. They are listed by frequency and then the (meter band). There are exceptions to every rule in Shortwave. Reception will vary when you are in a foreign country.

The CCRadio-SWP has plenty of memory. If you install active frequencies into memory, you can recall them easily. When you are trying to find a station, it is best to switch to manual tuning, using the tuning knob.

SWI

2300~2495 kHz (120m) - mostly tropical regions

3200~3400 kHz (90m) – mostly tropical regions

3900~4050 kHz (75m) – mostly Europe

4400~5100 kHz (60m) – night, mostly tropical

5800~6300 kHz (49m) – all year-round, night

7100~7600 kHz (41m) – best at night

Shortwave Tips

SWII

- 9250~9995 kHz (31m) all year, night/winter *
- 11.50~12.16 MHz (25m) summer: near sunset
- 13.57~13.87 MHz (22m) day and summer
- 15.00~15.825 MHz (19m) day and summer *
- 17.48~17.90 MHz (16m) day and summer
- 18.90~19.02 MHz (15m) day, not much
- 21.45~21.85 MHz (13m) day, not much

Shortwave broadcasters use Universal Time Coordinated (UTC) time to coordinate their shows. You can normally find a UTC time signal at 5,000, 10,000 or 15,000 kHz.

Station Log	
000	025
001	026
002	027
003	028
004	029
005	030
006	031
007	032
800	033
009	034
010	035
011	036
012	037
013	038
014	039
015	040
016	041
017	042
018	043
019	044
020	045
021	046
022	047
023	048
024	049

Station Log	
050	075
051	076
052	077
053	078
054	079
055	080
056	081
057	082
058	083
059	084
060	085
061	086
062	087
063	088
064	089
065	090
066	091
067	092
068	093
069	094
070	095
071	096

Stat	<u>ion</u>	Log

-	
100	125
101	126
102	127
103	128
104	129
105	130
106	131
107	132
108	133
109	134
110	135
111	136
112	137
113	138
114	139
115	140
116	141
117	142
118	143
119	144
120	145
121	146
122	147
123	148
124	149

S	<u>τа</u>	τı	0	n	L	0	Ç

150	175
151	176
152	177
153	178
154	179
155	180
156	181
157	182
158	183
159	184
160	185
161	186
162	187
163	188
164	189
165	190
166	191
167	192
168	193
169	194
170	195
<u>171</u>	196
172	197
173	198
174	199

Model: CCRadio-SWP

ANSI C63.4: 2003

THIS DEVICE COMPLIES WITH PART 15 OF THE FCC RULES. OPERATION IS SUBJECT TO THE FOLLOWING TWO CONDITIONS

- 1) THIS DEVICE MAY NOT CAUSE HARMFUL INTERFERENCE, AND
- THIS DEVICE MUST ACCEPT ANY INTERFER-ENCE RECEIVED, INCLUDING INTERFERENCE THAT MAY CAUSE UNDESIRED OPERATION.

Notice: Any changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.